



Model EL-WiFi-DTP+ is a dual-channel, WiFi-based, wireless data logger for time and date-stamped temperature measurements using the included temperature probes. They adhere to the 802.11b standard and can integrate with any new or existing WiFi network. The data loggers are powered by a built-in, re-chargeable battery to allow purely stand-alone performance, and are packaged in a small, IP43-rated enclosure to tolerate sprayed water environments. The included temperature probes are made of high temperature flexible cable with a stainless steel end cap rated for IP67 (immersible up to 1m). The data loggers are fully programmable, initially via a built-in USB interface, and thereafter wirelessly via the WiFi link using included Windows-based software. Programmable parameters include a unique logger name, channel name, °F or °C, logging rate, report rate, as well as temperature alarms. The same software acts as a repository for temperature data, which the data logger uploads at programmable periodic intervals. Built-in memory seamlessly buffers over 100 days of readings when contact is lost with the WiFi network, the software, or the PC on to which the software is running. When the connection is re-established the data logger transparently uploads its memory contents to the PC while still logging data. Data is stored on the host PC in comma-separated value (CSV) format, and the host program allows the graphical review of acquired temperature data along with a time and date stamp, and seamless data export to Microsoft Excel.

Features

- EL-WiFi-DTP+ provides high accuracy
- -40 to +125°C (-40 to +257°F) temperature measurements
- Thermistor probes IP rating of 67 resists dust and immersion
- Main unit IP rating of 43 resists water spray
- Built-in display shows current, min/max readings, alarm states
- Wireless communication to any PC using WiFi
- 802.11b-compliant for universal compatibility
- Built-in, rechargeable battery for independent deployment
- Seamlessly uploads memory to host PC at programmable intervals
- Huge buffer memory of 1,000,000 readings tolerates disconnects
- Programmable high/low alarm limits
- Built-in USB interface for battery charging and initial configuration
- Free configuration, review, and Excel-export software
- Supplied with mounting bracket, USB cable, splitter cable, two temperature probes, and two probe brackets.

Programmable Elements

- Logger Name, Channel Name
- °C, °F
- Logging Interval (10s, 1m, 5m, 30m, 1hr, 6hr, 12hr)
- High and Low Alarms for temperature
- Alarm Hold (on/off)

Buffer Depth*

Sampling Interval	Buffer Depth
1 sample every 10 seconds	> 100 days
1 sample every minute	years
1 sample every 5 minutes	years
1 sample every 30 minutes	years
1 sample every hour	years
1 sample every 6 hours	years
1 sample every 12 hours	years


* The maximum time that the data logger can remain disconnected from the WiFi network, host PC, or host software before losing data.

EL-WiFi-DTP+ Close-up



USB port sealed with rubber gasket

EL-WiFi-DTP+ in its included mounting bracket




Port for Temperature Probes




Two Probes Included

Included Y Splitter



EL-WiFi-DTP+ Major Operating Modes

Current measured values:



WiFi signal strength (“- -” to 10):



OR

Sync³
(uploading recorded data to host):



Maximum recorded values since reset:²



Minimum recorded values since reset:²



¹Flashes when not connected to WiFi router.

²Min and Max values may be reset from these screens by holding the button for three seconds.

³If the data logger is in its sleep mode after losing contact with the WiFi router, PC, or software for a lengthy period, cycling to this WiFi screen forces a reconnect.

EL-WiFi-DTP+ Specifications

Specification	Minimum	Typical	Maximum	Unit
Battery Life		>6*		Months
USB Supply Voltage	4.5		5.5	VDC
Temperature Measurement Range	-40 (-40)		+125 (+257)	°C (°F)
Internal Temperature Resolution		±0.01		°C
Temperature Accuracy (-15 to +80°C)		±0.2		°C
Temperature Accuracy (-40 to +125°C)		±0.6		°C
Probe Clip Operating Temperature	-40 (-40)		+100 (+212)	°C (°F)
Logging Rate (configurable)	10 seconds		12 hours	
Transmission Rate (configurable)	1 minute		24 hours	
Unit Operating Temperature	-20 (-4)		+60 (+140)	°C (°F)
Number of Loggers per PC			253	Loggers
Supported Security Standards	WEP 64 bit; WEP 128 bit; WPA-PSK; WPA2-PSK			

*Typical between charging cycles, but could be less if frequent transmissions.

WARNING: Do not exceed operating temperatures.

EL-WiFi-DTP+ Ordering Information

Description	Order Number
EL-WiFi-DTP+ Data Logger Includes data logger, mounting bracket, USB cable (1 meter), Y splitter cable, two temperature probes (3m), two probe clips, and software (downloadable).	EL-WiFi-DTP+
Optional Accessories	
101085 Power supply adapter (USB to AC) to power and charge the data logger's battery via a standard outlet. Without this the data logger can only be powered and charged from a PC's USB port. Includes US adapter (international adapters available below).	101085
101017-RPE European Adapter for power supply 101085.	101017-RPE
101017-RPK UK Adapter for power supply 101085.	101017-RPK
101017-RPS Australian Adapter for power supply 101085.	101017-RPS
101017-RPA SPARE US Adapter for power supply 101085 (one already ships with 101085).	101017-RPA

Included



EL-WiFi-DTP+ Data Logger



Mounting Bracket



Software (Via Download)



USB Cable (1 meter)

Two Temperature Probes (3m)

Two Probe Brackets

Optional Accessories



101085



101017-RPS



101017-RPK



101017-RPE




101017-RPA*

*USA adapter is included with purchase of 101085

Typical EL-WiFi Deployment Options and Built-in Fail Safe


EL-WiFi data loggers automatically detect and allow you to connect to any WiFi source that supports the 802.11b standard. Various connection options are supported, as well as a fail safe backup system to ensure that on-going recording and historical values are preserved and automatically uploaded to a host PC whenever it becomes available.

EL-WiFi Deployment Options



* Software may be installed on multiple PCs at the same time, but only one may access any given data logger at a time.

EL-WiFi Failsafe Ensures Continuous, Uninterrupted Recording




EL-WiFi products support a failsafe operation feature that ensures retained readings and data logging continuity in the event of failure at one or more communication junctions: between the data logger and the WiFi router; between the WiFi router and PC; PC shut down; EL-WiFi software shutdown.

In its failsafe mode, the data logger will attempt to transmit stored data at the interval set during configuration (every 1 to 100 readings.) If it cannot connect it will attempt to send data over the course of approximately the next minute. If that attempt fails, the data logger will wait for 15 minutes and try again, and in 15-minute epochs thereafter until connection is established and data is uploaded. During this time, the data logger continues to acquire data to its internal memory, so measurements are never lost. With a memory depth of 500,000 readings, the data logger must fail to connect for over 100 days at the fastest sample interval before data is lost.

Finally, you may manually force the data logger to test for a connection by pressing its control button until the WiFi signal strength screen appears, where the data logger will instantly wake up, connect (if possible), and upload data from its memory.

A Typical EL-WiFi Data Logger Configuration with Included Software


Start Software




Connect the Data Logger to the USB port




Configure Alarms




Select WiFi Gateway



Configure General Settings




Setup Successful!



Note: Configuration items are EL-WiFi model-dependent.

Working with WiFi Data Loggers



View Sensors



Click on the View Sensors Icon in the configuration software to view connected data loggers.

Overview of connected data loggers

This screen lists all the data loggers on the PC's network, and provides information about each:

- Data logger name and MAC address
- WiFi signal strength as detected by the sensor
- Data logger battery status
- Data logger alarm status (see below)
- The data logger's WiFi connection status (Connected, Waiting for sensor, Disconnected)
- A virtual real time picture of the data logger's display that updates as new data is transmitted.

Near the bottom of this display you can wirelessly adjust data logger settings; view a graph of sensor-acquired data; and mute the PC's audible alarm if any sensor is in the alarm state.



A typical alarm condition

When an EL-WiFi data logger enters an alarm state, that condition is clearly indicated on its status display with a red-flashing icon of an alarm bell. If the PC's internal speaker is enabled, a ringing alarm sounds as an audible indication of a detected alarm state.

Working With EL-WiFi Data Logger Data



A fast, graphical review of acquired data

Information acquired by any EL-WiFi data logger may be instantly reviewed, even while the sensor continues to acquire data. That's because it buffers a virtually unlimited amount of data in its non-volatile memory until the application can respond to retrieve it. This performance gives you the freedom to review acquired data whenever and for as long as you like.

The graphing utility allows a cursor to be pulled across acquired data to display values correlated with date and time of acquisition. Even programmed alarm limits are clearly defined. Tools that are accessible in a mouse-click allow you to save data, magnify and compress it for viewing, print the chart, and instantly export it to Microsoft Excel® (see below).

Note: Acquired and displayed quantities are EL-WiFi model-dependent.

File Export Facility


Microsoft Excel is generally one of the more common analysis utilities for acquired data. This popularity is embraced by the EL-WiFi Data Viewer. A single mouse-click instantly exports data into an Excel spreadsheet, ready for detailed analysis. This approach avoids annoying intermediate files and the need for Excel to convert them into compatible values. Of course, the data is also available as ASCII-delimited CSV (comma-separated values) for general-purpose use.

WiFi Sensor Time	Temperature(°C)	Low Alarm	Humidity(%rh)	Dew Point(°C)
1 13/07/2012 15:31:54	27.3	69.5	36	10.9
2 13/07/2012 15:32:04	27.3	69.5	36	10.9
3 13/07/2012 15:32:14	27.3	69.5	37	11.3
4 13/07/2012 15:32:24	27.3	69.5	37	11.3
5 13/07/2012 15:32:34	27.3	69.5	37	11.3
6 13/07/2012 15:32:44	27.3	69.5	37	11.3
7 13/07/2012 15:32:54	27.3	69.5	42	13.3
8 13/07/2012 15:33:04	27.3	69.5	39	12.1
9 13/07/2012 15:33:14	27.3	69.5	38	11.7
10 13/07/2012 15:33:24	27.3	69.5	37	11.3
11 13/07/2012 15:33:34	27.3	69.5	36	10.9
12 13/07/2012 15:33:44	27.4	69.5	36	11
13 13/07/2012 15:33:54	27.4	69.5	36	11
14 13/07/2012 15:34:04	27.4	69.5	36	11
15 13/07/2012 15:34:14	27.4	69.5	36	11
16 13/07/2012 15:34:24	27.4	69.5	36	11
17 13/07/2012 15:34:34	27.3	69.5	36	10.9
18 13/07/2012 15:34:44	27.3	69.5	36	10.9
19 13/07/2012 15:34:54	27.3	69.5	36	10.9
20 13/07/2012 15:35:04	27.3	69.5	36	10.9
21 13/07/2012 15:35:14	27.3	69.5	36	10.9
22 13/07/2012 15:35:24	27.3	69.5	36	10.9
23 13/07/2012 15:35:34	27.3	69.5	36	10.9
24 13/07/2012 15:35:44	27.3	69.5	36	10.9
25 13/07/2012 15:35:54	27.3	69.5	36	10.9
26 13/07/2012 15:36:04	27.3	69.5	36	10.9

Note: Acquired and displayed quantities are EL-WiFi model-dependent.

Cloud-based Device Management

When you setup any EL-WiFi product you have the option of managing the data logger locally from a PC running a Windows OS and located on the same subnet as the logger (as described above), or to perform management via a cloud server using *Files Thru The Air™* technology. Cloud server management with *Files Thru The Air™* offers the flexibility of managing and monitoring any number of devices from any location in the world with your smart phone, tablet, laptop, or desktop running any operating system and using only a web browser.



Files Thru The Air™ Cloud Management Features

Files Thru The Air™ technology puts you in control of your data. Local management is out, and remote management is in – from any location using any device that has a web browser:

- ✓ Accessible from any location, local or remote from the data logger's LAN
- ✓ Password-protected access using SSL sessions for security
- ✓ Supports all operating systems (all you need is a web browser)
- ✓ Supports all smart phones, tablets, laptops, and desktop computers
- ✓ Remote management, including all device settings:
 - Device name
 - Temperature scale
 - Sampling interval
 - Transmission period
 - Alarm Settings
- ✓ Instant email alerts to as many as 100 addresses:
 - When acquired data breaches definable limits
 - When there's an AC power outage
 - When a device's battery is low
 - When the device loses connection with the Cloud
 - When there's a device-specific problem
- ✓ Data storage in the cloud
- ✓ Cloud-based graphical and tabular data displays with date and time
- ✓ Optional services:
 - Audit trail export to provide a documentary record of changes
 - Multiple user access
 - Individual time zones per user
 - Recorded data printing and export
 - Unlimited data storage
 - Unlimited devices

Features

- Detects alarm conditions from any number of EL-WiFi data loggers
- Emits an audible alarm at one of 10 user-defined volume levels
- Includes nine unique alarm sounds
- Flashing red LEDs provide a visual alarm indicator
- A built-in, rechargeable battery keeps the unit functioning in the event of a power failure
- Includes free, downloadable configuration software
- 802.11b compliant




The EL-WiFi-Alert is a stand-alone hardware add-on for EL-WiFi series data loggers. The sole purpose of the EL-WiFi-Alert is to provide an audio/visual notification when one or more of your EL-WiFi series data loggers (installed on the same wireless network) indicates an alarm state.

Using the downloadable EL-WiFi-WIN software, you can choose from nine unique alarm tones and 10 volume levels. In addition to the audible alarm, a flashing LED indicator, housed under the translucent rear cover, provides a striking visual cue. The audible and LED alarm indicators can be enabled/disabled independently, and can be muted after a user-defined period of time, from 30 seconds to one hour.

The EL-WiFi-Alert is great complement to the built-in alarm indicators on all EL-WiFi series data loggers and in the PC based WiFi Sensor software. EL-WiFi-Alert units can be placed in secondary locations, out of sight of the EL-WiFi loggers themselves. When the EL-WiFi-Alert conveys an alarm, you can view the PC-based software to determine which unit(s) are in an alarm state. This added flexibility allows you to identify and respond to alarms that might otherwise go unnoticed.

Typical Deployment



EL-WiFi Data Logger Series

EL-WiFi Data Logger series products are a line of low cost, compact, battery-operated data loggers with wireless connectivity and an LED display. Each product in the line offers a specific measurement function and range.

Temperature Data Loggers -20 to +60°C (-4 to +140°F)

EL-WiFi-T
[Learn More](#)



Temperature and Humidity Data Loggers -20 to +60°C (-4 to +140°F) and 0 to 100% RH

EL-WiFi-TH
[Learn More](#)



EL-WiFi-T+
(Higher Accuracy)
[Learn More](#)



EL-WiFi-TH+
(Higher Accuracy)
[Learn More](#)



Temperature Data Loggers with Probe -40 to +125°C (-40 to +257°F)

EL-WiFi-TP
[Learn More](#)



Thermocouple Temperature Data Loggers -270 to +1300°C (-454 to +2372°F)

EL-WiFi-TC
[Learn More](#)



EL-WiFi-TP+
(Higher Accuracy)
[Learn More](#)



EL-WiFi-DTC
[Learn More](#)



EL-WiFi-DTP+
(Higher Accuracy)
[Learn More](#)



Lascar Data Logger Product Lines

EL-USB Data Loggers



Lascar EasyLog model EL-USB series products are a line of low cost, compact, battery-operated data loggers with built-in memory and a USB interface for easy setup and data download. Each product in the line offers a specific measurement function (including temperature, voltage, process current, and more).

EL-GFX Data Loggers



The EL-GFX line of data loggers is the latest release from Lascar Electronics with similar functionality of the EL-USB series with an added graphic display for data.

EL-WiFi Data Loggers



Lascar's EL-Wifi Data Logger series products are low cost, compact, battery-operated data loggers with wireless connectivity to any PC over a WiFi router. Each product in the line features a large, easy-to-read display of current measurements, and is purchased for specific measurement functions.



241 Springside Drive
Akron, Ohio 44333
Phone: 330-668-1444
Fax: 330-666-5434

Data Acquisition Product Links

(click on text to jump to page)

[Data Acquisition](#) | [Data Logger](#)